

05-26-00

HOPGOOD, CALIMAFDE, KALIL & JUDLOWE, LLP

COUNSELLORS AT LAW

LINCOLN BUILDING, 60 EAST 42ND STREET

NEW YORK, N.Y. 10165

jc714 U.S. PTO
09/578391
05/25/00

jc81
05/25/00
PTO

ROY C. HOPGOOD
JOHN M. CALIMAFDE
EUGENE J. KALIL
STEPHEN B. JUDLOWE, P.C.
DENNIS J. MONDOLINO
LEA B. WINKLER

JAMES M. BOLLINGER
BRIAN P. MURPHY
JANET B. LINN
BRADLEY N. RUBEN*
ROBERT G. GIBBONS
LISA M. FERRI

(212) 551-5000

TELECOPIERS

(212) 949-2795

(212) 949-9623

MICHAEL F. HURLEY

EDWARD M. REISNER

EVE KUNEN
JASON A. LIEF
RICHARD C. PETTUS
JEFFREY M. GOLD
GORDON F. BELCHER
KEITH T. TAKEDA
STEVEN R. BARTHOLOMEW*
JOHN F. GALLAGHER III
VIVEK S. SURI
DOUGLAS R. WEIDER*

MICHAEL H. IMBACUAN
DAVID GARROD
FRANK J. CHESKY III*
RICHARD J. MCCORMICK*
PHILIP L. HIRSCHHORN
ESTHER H. STEINHAEUER
VINCENT A. SIRECI
BRIAN W. NOLAN*
ANTHONY L. MEOLA
SYLVIA CHIOU

FRANCIS J. MURPHY
OF COUNSEL

POST OFFICE EXPRESS MAIL

File No. 0694-132

*NOT ADMITTED IN NEW YORK

Assist. Commissioner for Patents
Washington, D.C. 20231

Sir:

Enclosed herewith is the original application of Akiro Sato, Masao Suzuki and Akihisha Furukawa entitled ANASTOMOSIS MEMBER FOR ANASTOMOSIS OF BLOOD VESSELS AND ANASTOMOSIS METHOD USING THE ANASTOMOSIS MEMBER and comprising the following:

1. Specification (27) pages including twenty two (22) claims of which there are two (2) extra independent claims and 2 claims above 20 and including an Abstract;
2. Eight (8) sheets of drawings (Figs 1-16);
3. Declaration and Power of Attorney to follow;
4. Assignment in favor of the Tokin Corporation
5. Our firm check in the amount of \$882.00 for filing the application as follows:

Basic Fee	\$690.00
Two extra independent claims	156.00
Two claims in excess of 20	<u>36.00</u>
	<u>\$882.00</u>

6. Priority is claimed under 35 U.S.C.119 as follows:

<u>Country</u>	<u>Serial No.</u>	<u>Filing Date</u>
Japan	147278/1999	May 26, 1999
Japan	203318/1997	July 16, 1999

If there are any additional charges, please apply the cost to Account No. 08-2776.

Respectfully submitted,



Eugene J. Kalil
Registration No. 16,686
Hopgood, Calimfde, Kalil
& Judlowe
60 East 42nd Street
New York, New York 10165
Telephone: (212) 551-5000

Dated: May 25, 2000

CERTIFICATE OF MAILING
Under 37 C.F.R. §1.10

I hereby certify that this paper and those identified above, including any attached thereto, was deposited with the U.S. Postal Service as "Express Mail Post Office to Addressee" with the label number identified below and on the date identified below, and was deposited with sufficient first class postage and was addressed to:
Commissioner of Patents and Trademarks,
Washington, D.C. 20231.

May 25, 2000

Date


EL132002986US

Express Mail Label No.

Hamida Jaffer

Name

Signature



[illegible][illegible][illegible][illegible][illegible][illegible][illegible]

vessels to each other. Thus, the anastomosis is carried out. For example, a type of the stent is disclosed in U.S. Patent No. 6,017,362.

In the technique of anastomosing the blood vessels by the use of the stent, the blood vessels are simply press-fitted by the elasticity of the stent and may be undesirably released from each other by, for example, the beat of the artery. Thus, the anastomosis by the use of the existing stent is insufficient in fixing or engaging force and in reliability.

Summary of the Invention:

It is therefore a technical object of this invention to provide an anastomosis member capable of safely and quickly carrying out the anastomosis of blood vessels and to provide an anastomosis method using the anastomosis member.

It is another object of this invention to provide an anastomosis member improved in reliability by the use of a technique of applying an engaging force only to an adventitia of a blood vessel which is stronger than an intima of the blood vessel and to provide an anastomosis method using the anastomosis member.

It is still another object of this invention to provide an anastomosis member capable of carrying out the anastomosis of blood vessels substantially equal in outer diameter and in inner diameter and to provide an anastomosis method using the anastomosis member.

According to this invention, there is provided an anastomosis member to be arranged at an anastomosed site of first and second blood vessels to carry out the anastomosis of the first and the second blood vessels, the anastomosis member having a generally cylindrical body comprising at least one plate member to be brought into contact with both of the first and the second blood vessels, the plate member having a plurality of protrusions formed on at least one of opposite surfaces thereof to be engaged with at least one of the first and

the second blood vessels so as to prevent the dislocation of the first and the second blood vessels at the anastomosed site.

Preferably, the anastomosis member has a plurality of the generally cylindrical bodies and at least one connecting member connecting the generally cylindrical bodies to one another.

Preferably, the anastomosis member has an elasticity so as to be compressed and expanded in diameter.

Preferably, the anastomosis member has a stress-strain characteristic including a plurality of different kinds of regions at least corresponding to a low-rigidity part deformable along the curvatures of the first and the second blood vessels to be tightly fitted thereto, and a spring region which is compressible and self-expandable in diameter.

Preferably, the generally cylindrical body comprises a plurality of the plate members connected to one another in a zigzag pattern.

Preferably, the generally cylindrical body comprises at least one plate member wound into a helical shape

Preferably, the generally cylindrical body comprises a plurality of the plate members connected to one another in a lattice pattern.

Preferably, the generally cylindrical body comprises a plurality of the plate members connected to one another in a rhombic pattern.

Preferably, the generally cylindrical body comprises a plurality of the plate members arranged in parallel to one another and a plurality of connecting members connecting the plate members to one another.

Preferably, each of the connecting members is an elastic wire member.

Preferably, the plate member is made of a stainless steel plate or a shape memory alloy selected from a TiNi alloy and a beta Ti alloy.

According to this invention, there is also provided an anastomosis device for use in the anastomosis of first and second blood vessels, the

09573341.06600

anastomosis device comprising a combination of an anastomosis member arranged on an outer surface of at least one of the first and the second blood vessels and a stent to be arranged in a lumen of the at least one of the first and the second blood vessels, the anastomosis member having a generally cylindrical body comprising at least one plate member to be brought into contact with both of the first and the second blood vessels, the plate member having a plurality of protrusions formed on at least one of opposite surfaces thereof to be engaged with at least one of the first and the second blood vessels.

Preferably, the stent is made of a stainless steel plate or a shape memory alloy selected from a TiNi alloy and a beta Ti alloy.

Preferably, the anastomosis device further comprises an additional blood vessel.

According to this invention, there is also provided an anastomosis method for the anastomosis of first and second blood vessels by the use of an anastomosis member to be arranged at an anastomosed site of the first and the second blood vessels, the anastomosis member having a generally cylindrical body comprising a plate member with a plurality of protrusions formed on at least one of opposite surfaces thereof, the method comprising the steps of inserting the anastomosis member into lumens of the first and the second blood vessels; bringing the plate member into contact with at least one of the first and the second blood vessels; and engaging the first and the second blood vessels with the protrusions so as to prevent the dislocation of the first and the second blood vessels at the anastomosed site.

Preferably, the anastomosis method further comprises the steps of inserting an end portion of one of the first and the second blood vessels into the lumen of the other blood vessel so that the end portions of the first and the second blood vessels overlap each other with the protrusions engaged with at least one of the first and the second blood vessels.

Preferably, each of the plate members is sutured by a fastening member to one of the first and the second blood vessels in at least one position in the anastomosed site, the protrusions being formed only on one surface of the plate member which faces the other of the first and the second blood vessels at the anastomosed site.

According to this invention, there is also provided an anastomosis method for the anastomosis of first and second blood vessels by the use of an anastomosis device to be arranged at an anastomosed site of the first and the second blood vessels, the anastomosis device comprising a combination of an anastomosis member and a stent, the anastomosis member comprising a plate member with a plurality of protrusions formed on at least one of opposite

surfaces thereof, the method comprising the steps of inserting the stent to extend over lumens of the first and the second blood vessels; abutting the first and the second blood vessels to each other; arranging the anastomosis member around outer surfaces of the first and the second blood vessels; bringing the protrusions into contact with an adventitia of each of the first and the second blood vessels; and engaging the first and the second blood vessels with the protrusions so as to prevent the dislocation of the first and the second blood vessels at the anastomosed site.

Preferably, the anastomosis method further comprises the steps of placing an additional blood vessel on the outside of the anastomosis member arranged around the outer surfaces of the first and the second blood vessels; and engaging the anastomosis member and the additional blood vessel with the protrusions.

Preferably, the additional blood vessel is fastened by a fastening member in at least one position.

Preferably, the fastening member is a filament or a strap.

Brief Description of the Drawing:

Fig. 1 is a perspective view of an astomosis member according to a first embodiment of this invention;

Fig. 2 is a perspective view of an astomosis member according to a second embodiment of this invention;

Fig. 3 is a perspective view of an anastomosis member according to a third embodiment of this invention;

Fig. 4 is a perspective view of an anastomosis member according to a fourth embodiment of this invention;

Fig. 5 is a perspective view of an anastomosis member according to a fifth embodiment of this invention;

Fig. 6 is a perspective view of an anastomosis member according to a sixth embodiment of this invention;

Fig. 7 is a perspective view of an anastomosis member according to a seventh embodiment of this invention;

Fig. 8 is a perspective view of an anastomosis member according to an eighth embodiment of this invention;

Fig. 9 is a development view showing the eighth anastomosis member of in Fig. 8;

Fig. 10 is a transversal sectional view illustrating a first anastomosis example of blood vessels using the first anastomosis member of Fig. 1;

Fig. 11 is a transversal sectional view illustrating a second anastomosis example of blood vessels using the fifth anastomosis member of Fig. 5;

Fig. 12 is a transversal sectional view illustrating a third anastomosis example using a two-piece anastomosis device;

Fig. 13 is a transversal sectional view illustrating a fourth anastomosis example using a three-piece anastomosis device;

Fig. 14 is a deployed plan view of an anastomosis member according to a ninth embodiment of this invention;

Fig. 15 is a transversal sectional view illustrating a fifth anastomosis example using a composite anastomosis device; and

Fig. 16 is a cross-sectional view taken along in a line XVI-XVI in Fig. 15.

Description of the Preferred Embodiments:

Now, description will be made about several preferred embodiments of this invention with reference to the drawing.

At first referring to Fig. 1, an anastomosis member 11 according to a first embodiment of this invention has a generally cylindrical body comprising a plurality of plate members or sections 11a connected to one another in a zigzag pattern extending along a cylindrical surface of an imaginary tube. Each of the

[illegible][illegible][illegible][illegible][illegible][illegible]

11 / 37

09703030250

CONFIDENTIAL

、候、心、計、事、務、所

10:07'07-0 -00

For example, each of the plate members 14a comprises a stainless steel plate subjected to annealing and having a low rigidity. For example, each of the

Specifically, the anastomosis member 14 has a low-rigidity part (plate members 14a) deformable along the curvatures of first and second blood vessels (Fig. 10, 33 and 34) to be tightly fitted thereto, and a self-expandable spring part (connecting members 14c). Thus, the anastomosis member 14 has a stress-strain characteristic including at least two different kinds of regions.

The protrusions 14b are formed on the opposite surfaces of each plate member 14a. The plate members 14a and the connecting members 14c are welded to each other to form the generally cylindrical body as the anastomosis member 14. The anastomosis member 14 can be expanded and compressed by changing the angles of the angled portions of the connecting members 14c.

As described above, the plate members 14a and the connecting members 14c are different from each other in stress-strain characteristic. The plate members 14a are soft and low in rigidity. Therefore, the anastomosis member 14 is readily deformable in conformity with the curvatures of the first and the second blood vessels without local pressure concentration in the first and the second blood vessels. Thus, the anastomosis member 14 can uniformly apply the pressure upon the first and the second blood vessels. Because of presence of the protrusions 14b, the anastomosis member 14 can be engaged with the first and the second blood vessels with a large frictional force.

It is noted here that the shape of the anastomosis member 14 is not restricted to that illustrated in Fig. 4. The connecting member 14c can be

Referring to Figs. 8 and 9, an anastomosis member 18 according to an eighth embodiment of this invention comprises a pair of generally cylindrical bodies connected by a connecting portion 18c. Each of the generally cylindrical bodies is similar in structure to the generally cylindrical body of the anastomosis member 14 in Fig. 4. The connecting portion 18c is made of a material same

as that of plate members 14a. The connecting portion 18c is smaller in width than each plate member 14a.

In the foregoing embodiments, the plate members 11a, 12a, 13a, and 14a are provided with the protrusions 11b, 12b, 13b, and 14b formed on both of the opposite surfaces thereof, respectively. Alternatively, the protrusions may be formed on only one of the opposite surfaces thereof. Each of the anastomosis members 11 through 18 is not restricted to the pattern described in each of the foregoing embodiments but may have any appropriate pattern as far as the diameter can flexibly be changed.

As a material of each of the plate members 11a, 12a, 13a, and 14a in the foregoing embodiments, use may be made of a stainless steel plate, a TiNi alloy and a TiNi-X alloy (X = Cr, V, Cu, Fe, Co, etc) having superelasticity at a living body temperature. Furthermore, use may also be made of a wide variety of shape memory alloys, such as a Cu-based alloy and a Fe-based alloy, as well as a beta Ti alloy. Taking the biocompatibility and the toxicity into consideration, the opposite surfaces of the plate members 11a, 12a, 13a, and 14a may be coated with titanium or the like.

Now, description will be made of several specific examples of the anastomosis of the first and the second blood vessels.

Referring to Fig. 10, a first example of the anastomosis will be described. Herein, the anastomosis is carried out by the use of the anastomosis member 11 illustrated in Fig. 1. In the following description, the similar parts are designated by like reference numerals. It will be noted here that the size of the anastomosis member 11 in this example is slightly different from that mentioned in conjunction with Fig. 1.

As illustrated in Fig. 10, the anastomosis member 11 is arranged over a host blood vessel 33 as the first blood vessel and an artificial blood vessel 34 as the second blood vessel. An end portion of the artificial blood vessel 34 is

Since the anastomosis member 11 comprises the plate members 11a connected in a zigzag pattern, the anastomosis member 11 can be brought into contact with the host and the artificial blood vessels 33 and 34 to expand the host and the artificial blood vessels 33 and 34 independently of each other. Because the protrusions 11b provide a large frictional force, the anastomosis member 11 can be securely engaged with the intimae of the host and the artificial blood vessels 33 and 34. Therefore, even under the beat of the artery, the dislocation of the host and the artificial blood vessels 33 and 34 with respect to each other can be avoided by the use of the anastomosis member 11.

By a hand of a surgeon, the anastomosis member 11 is inserted into lumens of the host and the artificial blood vessels 33 and 34. For example, if the artificial blood vessel 34 has a diameter of 6mm, the anastomosis member 11 is compressed to a reduced diameter of 6mm or less and then inserted into the lumen of the artificial blood vessel 34. Furthermore, the anastomosis member 11 is inserted also into the lumen of the host blood vessel 33. The host and the artificial blood vessels 33 and 34 are made to approach each other to form an overlapping portion. At this time, the anastomosis member 11 is self-expanded from a compressed state. Therefore, the anastomosis can be quickly and easily carried out.

From the foregoing description, it will readily be understood that the anastomosis members 12, 13, and 14 illustrated in Figs. 2 through 4 may also be used instead of the anastomosis member 11. In this case also, the end portions of the host and the artificial blood vessels 33 and 34 can be expanded independently of each other so that the anastomosis is reliably carried out.

As illustrated in Fig. 11, the anastomosis member 15 is attached to the host blood vessel 33 and the artificial blood vessel 34. The anastomosis member 15 is arranged over the lumens of the host and the artificial blood vessels 33 and 34 to be anastomosed. The end portion of the artificial blood vessel 34 is inserted into the end portion of the host blood vessel 33.

From the foregoing description, it will readily be understood that the anastomosis members 16, 17, and 18 illustrated in Figs. 6 through 8 may also be used instead of the anastomosis member 15. In this case also, the end portions of the host and the artificial blood vessels 33 and 34 can be engaged by the anastomosis member 15 to be expandable independently of each other. Thus, the anastomosis is reliably carried out.

[illegible]

As illustrated in Fig. 12, the anastomosis member 11 is arranged in an anastomosed site between the host blood vessel 33 and the artificial blood vessel 34. The end portion of the artificial blood vessel 34 is inserted into the end portion of the host blood vessel 33. At the anastomosed site, the end portions of the host and the artificial blood vessels 33 and 34 overlap each other with the anastomosis member 11 interposed therebetween. In the lumen of the artificial blood vessel 34 at the anastomosed site, the stent 36 is arranged.

For example, the stent 36 comprises a shape memory alloy such as a TiNi alloy having a cylindrical shape and a lattice pattern. For example, the stent 36 is designed to have a cylindrical shape with a final expanding diameter of 7mm. The stent 36 has an axial length of 10mm. The stent 36 has superelasticity at and around the body temperature of the living body.

As illustrated in Fig. 12, the stent 36 expands the artificial blood vessel 34 outwards in a radial direction. The stent 36 is inserted into the lumen of the artificial blood vessel 34 having an outer diameter of 6mm and an inner diameter of 5mm. Then, the artificial blood vessel 34 is inserted into the host blood vessel 33 with the anastomosis member 11 interposed between the host and the artificial blood vessels 33 and 34.

The host and the artificial blood vessels 33 and 34 and the anastomosis member 11 are press-fitted by the stent 36. At this time, the protrusions 11b are engaged with the intima of the host blood vessel 33 and the adventitia of the artificial blood vessel 34. Thus, the host and the artificial blood vessels 33 and 34 are prevented from being dislocated even under the beat of the artery. Thus, the anastomosis is reliably carried out.

The stainless steel plate of the anastomosis member 11 is not restricted to SUS316 but may be any other appropriate product having a low rigidity and a flexibility. The material and the shape of the stent 36 are not restricted to those given in this embodiment but may be appropriately selected taking into account

18 / 37

181335030250

CALIFORNIA

10:07:07-0 -00

More specifically, the anastomosis member 11 comprises a strip-like plate member 11a made of a stainless steel plate (SUS316) subjected to

annealing and having a low rigidity. The plate member 11a has a thickness of 0.25mm. Each protrusion 11b has a height between 65 and 75 μ m and a diameter of 30 μ m. The protrusions 11b are formed at a pitch of 0.2mm.

In this example of the anastomosis, the anastomosis member 11 has an inner diameter of 8mm, an axial length of 10mm, and a width of 0.4mm. The anastomosis member 11 is flexibly variable in shape and in cylindrical diameter.

The stent 46 is made of a material similar to that of the stent 36 illustrated in Fig. 12 and has a lattice pattern. For example, the stent 46 is designed to have a cylindrical shape with a final expanding diameter of 7mm and an axial length of 20mm.

In the anastomosis, one axial half of the stent 46 is inserted into the lumen of the artificial blood vessel 34, for example, having an outer diameter of 8mm and an inner diameter of 6mm. Then, the host and the artificial blood vessels 33 and 34 are abutted to each other. Simultaneously, the other axial half of the stent 46 is inserted into the lumen of the host blood vessel 33. The anastomosis member 11 preliminarily arranged on the outside of the artificial blood vessel 34 is positioned to extend over the outer surfaces of both of the host and the artificial blood vessels 33 and 34. Likewise, the additional blood vessel 55 arranged on the outside of the artificial blood vessel 34 is positioned around the anastomosis member 11. The additional blood vessel 55 has an inner diameter of 8.1mm.

The opposite ends of the additional blood vessel 55 are fastened by the filament 57 as the fastening member to the outer surfaces of the host and the artificial blood vessels 33 and 34. The host and the artificial blood vessels 33 and 34 and the anastomosis member 11 are press-fitted by an internal pressure applied by the stent 46 and an external pressure applied by the additional blood vessel 55 fastened by the filament 57. At this time, the protrusions 11b are engaged with the host and the artificial blood vessels 33 and 34. Thus, the host

and the artificial blood vessels 33 and 34 are prevented by the anastomosis member 11 from being dislocated with respect to each other even under the beat of the artery. Therefore, the anastomosis is reliably carried out. Since the additional blood vessel 55 and the filament 57 are fastened to each other, blood leakage from the anastomosed site to the outside is prevented.

The anastomosis in the above-mentioned example can be manually and quickly carried out by a surgeon so that the time of interrupting the blood flow can be shortened.

In this example of the anastomosis, the engaging force of the protrusions 11b acts only on the adventitia of each blood vessel which is relatively strong as compared with the intima. Thus, the load upon the host and the artificial blood vessels 33 and 34 is small as compared with the case where the inner surfaces are used in engagement. Furthermore, the host and the artificial blood vessels 33 and 34 need not overlap each other so that the anastomosis is possible even if the host and the artificial blood vessels 33 and 34 are substantially equal in diameter to each other. The anastomosis member 11 can relatively flexibly cope with the difference in size between the host and the artificial blood vessels 33 and 34.

The anastomosis member 11 is not restricted to the pattern described above but may have any pattern as far as the cylindrical diameter is flexibly variable. The material of the anastomosis member 11 is not restricted to the stainless steel plate but may be any appropriate material having a low rigidity and a flexibility.

The stent 46 is not restricted to the shape described above but may have any shape as far as an appropriate expanding force is provided so as to engage the host and the artificial blood vessels 33 and 34 and the anastomosis member 11 with one another. For example, use may be made of various kinds of stents typically used for expanding constricted portions of blood vessels.

Referring to Fig. 14, an anastomosis member 111 according to a ninth embodiment of this invention comprises a plurality of plate members 111a although only one is illustrated in the figure. Each plate member 111a is provided with a plurality of protrusions 111b formed on only one of its opposite surfaces. The plate member 111a is substantially similar to the plate member 11a illustrated in Fig. 1 except that a plurality of through holes 111f are formed along its center line parallel to a longitudinal direction thereof. The through holes 111f allow a suture filament (not shown) to pass therethrough. The plate members 111a are sutured to the artificial blood vessel 34 by the suture filament passing through the through holes 111f.

Referring to Figs. 15 and 16, a fifth example of the anastomosis will be described. Herein, the anastomosis is carried out by the use of a composite anastomosis device comprising a combination of the anastomosis member 111 in Fig. 14 and a woven tubular stent 136. The stent 136 is substantially similar to the stent 36 illustrated in Fig. 12.

The plate members 111a are sutured to the artificial blood vessel 34 with their surfaces having the protrusions 111b faced outward. In the example being illustrated in Fig. 16, eight plate members 111a are arranged on the outer surface of the artificial blood vessel 34 to form an octagonal shape around the center axis of the artificial blood vessel 34.

As illustrated in Fig. 15, the stent 136 is inserted into the lumen of the artificial blood vessel 34. The end portion of the artificial blood vessel 34 is inserted into the end portion of the host blood vessel 33. At this time, the plate members 111a are arranged between the blood vessels 33 and 34 overlapping each other. The protrusions 111b formed on the one surface of the plate members 111a sutured to the artificial blood vessel 34 are faced to the inner surface of the host blood vessel 33. The host blood vessel 33 and the plate members 111a are press-fitted by a pressing force of the stent 136 and the host

05978391-059900

blood vessel 33 is engaged by the protrusions 111b. Thus, the host and the artificial blood vessels 33 and 34 are prevented from being dislocated with respect to each other. Thus, the anastomosis is reliably carried out.

The shape and the number of the plate members 111a are not restricted to those given in this embodiment but may be appropriately selected so that the host and the artificial blood vessels 33 and 34 are reliably engaged by the protrusions 111b.

In the foregoing, description is directed to the anastomosis of the host blood vessel 33 and the artificial blood vessel 34 inserted into the host blood vessel 33. However, this invention is also applicable to the case where the host blood vessel 33 is inserted into the artificial blood vessel 34 in dependence upon the condition of the host blood vessel 33. It will readily be understood that this invention is also applicable to the case where the first and the second blood vessels are both living blood vessels.

As described above, according to this invention, the anastomosis member having protrusions are arranged at the anastomosed site of the first and the second blood vessels so that the engaging force for engaging the first and the second blood vessels can be increased. The anastomosis member can achieve the safe anastomosis not only in a normal blood vessel but also in a diseased blood vessel. Furthermore, the anastomosis of the first and the second blood vessels can be quickly carried out.

The anastomosis member of this invention is highly reliable because the protrusions can be formed so that the engaging force acts only on the adventitia of each blood vessel which is stronger than the intima.

The anastomosis member can be attached to the first and the second blood vessels which are abutted at their end faces to each other with the stent inserted into the lumens of the first and the second blood vessels. Therefore, it is possible to carry out the anastomosis for the first and the second blood

0957391-053900

The anastomosis member can be arranged on the outside of the first and the second blood vessels. Furthermore, the additional blood vessel can be arranged on the outside of the anastomosis member and fastened by a filament or a strap in at least one position. With this structure, it is possible to exert a greater engaging force and to assure a sufficient fixing force. By the use of the additional blood vessel, it is possible to effectively prevent the blood leakage out of the anastomosed site.

Finally, the anastomosis member is readily deformable in correspondence to the curvatures of the first and the second blood vessels. Therefore, it is possible to uniformly apply the pressure to the first and the second blood vessels without causing local concentration of the pressure.

24 / 37

- 10-07-07-0000, 10-07-07-0000, 10-07-07-0000

13. An anastomosis device as claimed in claim 12, wherein said stent is made of a stainless steel plate or a shape memory alloy selected from a TiNi alloy and a beta Ti alloy.

15. An anastomosis method for the anastomosis of first and second blood vessels by the use of an anastomosis member to be arranged at an anastomosed site of said first and said second blood vessels, said anastomosis member having a generally cylindrical body comprising a plate member with a plurality of protrusions formed on at least one of opposite surfaces thereof, said method comprising the steps of:

bringing said plate member into contact with at least one of said first and said second blood vessels; and

16. An anastomosis method as claimed in claim 15, further comprising the steps of inserting an end portion of one of said first and said second blood vessels into the lumen of the other blood vessel so that the end portions of said first and said second blood vessels overlap each other with said protrusions engaged with at least one of said first and said second blood vessels.

17. An anastomosis method for the anastomosis of first and second blood vessels by the use of an anastomosis device to be arranged at an anastomosed site of said first and said second blood vessels, said anastomosis device comprising a combination of an anastomosis member and a stent, said anastomosis member comprising a plate member with a plurality of protrusions formed on at least one of opposite surfaces thereof, said method comprising the steps of:

inserting the end portion of said one of the first and the second blood vessels into an end portion of a lumen of the other of said first and said second blood vessels;

inserting said anastomosis member so that said anastomosis member is interposed between said first and said second blood vessels at an anastomosed site where said first and said second blood vessels overlap each other;

bringing said protrusions into contact with said first and said second blood vessels;

press-fitting by said stent said first and said second blood vessels at said anastomosed site;

engaging said first and said second blood vessels with said protrusions so as to prevent the dislocation of said first and said second blood vessels at said anastomosed site.

18. An anastomosis method as claimed in claim 17, wherein each of said plate members is sutured by a fastening member to one of said first and said second blood vessels in at least one position in said anastomosed site, said protrusions being formed only on one surface of said plate member which faces the other of said first and said second blood vessels at said anastomosed site.

19. An anastomosis method for the anastomosis of first and second blood vessels by the use of an anastomosis device to be arranged at an anastomosed site of said first and said second blood vessels, said anastomosis device comprising a combination of an anastomosis member and a stent, said anastomosis member comprising a plate member with a plurality of protrusions formed on at least one of opposite surfaces thereof, said method comprising the steps of:

engaging said first and said second blood vessels with said protrusions so as to prevent the dislocation of said first and said second blood vessels at said anastomosed site.

21. An anastomosis method as claimed in claim 20, wherein said additional blood vessel is fastened by a fastening member in at least one position.

22. An anastomosis method as claimed in claim 21, wherein said fastening member is a filament or a strap.

25 / 37

0 9 2 0 3 0 5 3 8 1 8 ;




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8






FIG. 12




FIG. 13

